Options and Accessories



Lighting Package*



Turn Signals



One-Piece Windshield



Fold-Down Windshield



West Coast Mirror/ Heavy-Duty Bumper



Fold-Down Seat



Post-Mounted Safety Strobe



Certified ROPS
Cab Enclosure



Heavy-Duty Batteries



Glove BoxWith Lock

With Lock

Hour Meter



Extra-Traction Tires



Communication Display Module



Сапору Тор



3-Sided Enclosure

*Headlights, Taillights, Brakelights and Horn



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com







TransPorter

6


Need more passenger capacity?
The TransPorter 6 offers you just that: room for six. It allows you to offer passengers convenient transportation around the facility or throughout the grounds. For those demanding jobs, every TransPorter model offers




hard body construction, independent front suspension and semi-independent rear suspension — standard. So you can expect a tough, durable exterior while enjoying a smooth, stable ride.



Features



available)





Standard Color: Dark Gray



ArmorFlex®

fade-resistant











6-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension

Additional Features

- Maximum speed of 17 mph (27.3 kph) (Electric vehicles only)
- 1,500 lb (681 kg) total vehicle capacity
- Seating for six
- Maximum hp @
 3,600 rpm exceeds SAE
 J1940 Performance
 Standards
- Redesigned hip restraint for maximum styling and comfort
- 48-volt IQ Plus electric motor or 351 cc, 11.5 hp gas, pedal-start engine
- Headlights, taillights, brakelights and horn
- Reconfigured dash
- Side fuel fill

-	ecifications	with exclusive IQ Plus System	
POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt Shunt/Sepex	N/A
	Horsepower	3.7 @ 3400 rpm (continuous) 21.0 @ 2000 rpm (peak)	11.5**
	Governor	N/A	Automatic ground speed sensing, Internally geared-in unitized transaxle
	Governed RPM	N/A	3050 ± 30
	Ignition	N/A	Electronic w/electronic RPM limiter
	Drive Unit	12.3:1 direct-drive axle, double reduction helical gear	Unitized Transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	48-volt	12-volt, 500 cca 105 min. reserve
	Batteries	Eight 6-volt, Standard:T105 = 115 min @ 75 amps; Heavy Duty:T145 = 145 min @ 75 amps	N/A
	Charger	Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; International CE marked available	N/A
	Controller	500 amp Solid State	N/A
STEERING/ SUSPENSION	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shock
	Rear Suspension	Leaf springs with dual hydraulic shocks	Leaf springs with dual hydraulic shocks
	Brakes	Four Wheel Mechanical Drum	Four Wheel Mechanical Drum
	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	All aluminum	All aluminum
	Body Finish	Matching paint over molded in color	Matching paint over molded in color
	Light Package	Std. Light Package	Std. Light Package
	Front Tires	18 x 6.50-8, 6-ply rated, Premium tread	18 x 6.50-8,6-ply rated, Premium tread
	Rear Tires	18 x 8.50-8, 6-ply rated, Premium tread	18 x 8.50-8,6-ply rated, Premium tread
	Instrumentation	Battery capacity indicator, battery warning light	Battery capacity indicator, battery warning light
DIMENSIONS	Total Vehicle Capacity	1500 lb.(681 kg)	1500 lb.(681 kg)
	Overall Length	133" (337.8 cm)	133" (337.8 cm)
	Overall Width	49.3" (125.2 cm)	49.3" (125.2 cm)
	Overall Height	48.0" (121.9 cm)	48.0" (121.9 cm)
	Wheelbase	98.5" (250.2 cm)	98.5" (250.2 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7 gallons (26.5 liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight	717 lb.(325.5 kg)	842 lb. (382.3 kg)
	Speed Range	5 - 17 mph (8-27.3 kph)	14 - 16 mph (22.5-25.7 kph)
	Outside Clearance Circle	24.7 ft.(7.5 m) dia.	24.7 ft. (7.5 m) dia.
	Turning Radius	12 ft.(3.7 m)	12 ft. (3.7 m)
	Intersecting Aisle Radius	90" (228.6 cm)	90" (228.6 cm)
	Vehicle Warranty	2-year limited*	2-year limited