Attachments / Bucket, Rock - Loaders **Specifications**

 \times

Standard Optional N/A Not Applicable

	Bucket, Rock - 62"	Bucket, Rock - 68"	Bucket, Rock - 74"	Bucket, Rock - 82"
\ominus General				
Operating Weight	259 kg	281 kg	303 kg	325 kg
Length	1196 mm	1196 mm	1196 mm	1196 mm
Width	1572 mm	1727 mm	1880 mm	2083 mm
Height	528 mm	528 mm	528 mm	528 mm
Tines	17	19	21	23
Tine Thickness	10 mm	10 mm	10 mm	10 mm
\ominus Bucket Specs				
ISO Heaped Capacity	n/a	n/a	n/a	n/a

150 heaped bapacity	11/4	TI/a	11/4	TI/a
ISO Struck Capacity	n/a	n/a	n/a	n/a
Predrilled For	n/a	n/a	n/a	n/a

\bigcirc Compatible Carriers

Skid-Steer Loaders					
Bobcat A770			•	•	
Bobcat S450		•			
Bobcat S510		•			
Bobcat S530		•			
Bobcat S550		•			
Bobcat S570		•			
Bobcat S590		•			
Bobcat S595		•			
Bobcat S630		•	•	•	
Bobcat S650		•	•	•	
Bobcat S740		•	•	•	
Bobcat S750		•	•	•	
Bobcat S770		•		•	
Bobcat S850					

Compact Track Loaders		
Bobcat T450		
Bobcat T550		
Bobcat T590		
Bobcat T630		•
Bobcat T650		•
Bobcat T740		•
Bobcat T750		•
Bobcat T770		•
Bobcat T870		•

Toolcat™ Work Machine			
Bobcat Toolcat 5600		•	
Bobcat Toolcat 5610	•	•	

Telehandler			
Bobcat V417		•	•

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.